

Manufactured by:



# E330 FOCUS AX + E350 AX SD Singlephase

## The Next Generation of Advanced Residential Metering

The FOCUS AX SD is an advanced meter platform with features that rival any meter in its class. With available service disconnect integrated into the meter base, utilities can take advantage of the 200 Amp relay to disconnect power or limit service remotely using an advanced metering technology or manually at the meter. The combination of the FOCUS Service Disconnect base module and powerful AX register provides a flexible system that supports a variety of connect/disconnect and service-limiting applications.

A single circuit board design, mounted at the front of the meter, allows room for modular advanced metering communications or a KYZ option output board. Fewer parts and connectors throughout the board design increase reliability and contribute to better overall endpoint performance. Highly accurate load performance and the use of a field-proven Digital Multiplication Measurement Technique ensure reliability and dependability during the entire life of the FOCUS meter.

Meter reconfiguration can be accomplished optically through the configuration port located on the front cover.

- Select from displayable positive, negative, net and added (security) metrics
- Change the displayed information, order or digits
- Configure a CT/PT meter multiplier to obtain a direct reading
- Preset or reset kWh

With a focus on customer satisfaction, we are committed to providing the best metering solution in terms of capability, technology and affordability. By utilizing our experience and technology with that of our strategic allies and development partners, we provide metering solutions that cover the range of utilities' residential metering needs.



### Key Benefits

- **Digital Multiplication Measurement technique**
- **Non-volatile memory**
- **Designed for a 20 + year life**
- **Meets or exceeds industry and ANSI standards**
- **Uses ANSI protocol (between meter and advanced metering device)**
- **6 digit LCD and 3 Alpha ID**
- **Selectable meter multiplier**
- **Service limiter function**
- **Event log of 500 + entries**
- **77 kb of load profile memory, 1-8 channels**
- **Advanced second generation over-the-air-flashable firmware**



pazifik  
power

www.ppi.ph

**Specifications**

General Specifications	Active Energy "kWh-kW" meter	
	Digital Multiplication Measurement Technique	
	Non-Volatile memory	
	Designed for 20+ years life	
	Meets ANSI standards for performance	
	Utilizes ANSI protocol (between meter and AMI device)	
	9-Digit LCD	
	Display scroll sequence programmable (factory or end user)	
	Configuration Port-cover does not have to be removed or optional ANSI C12.18 optical port available	
Operating Temperature	-40°C to +85°C under cover	
Nominal Voltage	120V or 240V	
Operating Voltage	80% to 115% of Vn	
Frequency	60Hz +/-5%	
Humidity	5% to 95% relative humidity, non condensing	
Starting Load (Watts)	Class 20	0.005 Amp (0.6W)
	Class 100	0.030 Amp (3.6W)
	Class 200	0.050 Amp (12W)
	Class 320	0.080 Amp (19.2W)
	Class 480	0.120 Amp (28.8W)
Voltage Burden	≤ 1.9W Max	
Load Performance Accuracy	Accuracy Class 0.2%	
Available Forms	Self-Contained	1S, 2S, 2SE, 12S, 25S
	Transformer Rated	3S, 4S
	K-Base	2K
Display Options	Energy Metrics: +kWh, -kWh, Net kWh, and added kWh (Security)	
	Metric Energy Display Format - 4x1, 4x10, 5x1, 5x10, 6x1, or 6x10	
	Time of Use and Demand Billing	
AMI Platform	Modular or Integrated	
Selectable Meter Multiplier	Up to 4096 as result of PT ratio CT ratio	
Applicable Standards	ANSI C12.1 for electric meters	
	ANSI C12.10 for physical aspects of watt hour meters	
	ANSI C12.18 Protocol specifications for ANSI Type 2 Optical Port	
	ANSI C12.19 Utility Industry End Device Data Tables	
	ANSI C12.20 for electricity meters, 0.2 and 0.5 accuracy classes	
	CAN3-C17-M84 Canadian specifications for approval of type of electricity meters	
Service Disconnect	10,000 operations at full rated current (disconnect/connect)	
	Available forms: 1S, 2S, 12S, 25S	

**Discover how we can help you with quality  
and efficient solutions that will improve your business.  
Contact us at (02) 867 5620 or email us at [info@ppi.ph](mailto:info@ppi.ph).**

▶ SCAN ME


[www.ppi.ph/dlfiles/LGFSAX.pdf](http://www.ppi.ph/dlfiles/LGFSAX.pdf)

4/F South Park Plaza, Santiago  
Street Paseo de Magallanes  
Commercial Center, Makati City,  
1232 Philippines

#8 Lapu-Lapu St., Magallanes Village, Makati City, 1232 Philippines  
Tel.: +63 2 6288000, 5118888 Fax: +63 2 8364323  
Email: [info@ppi.ph](mailto:info@ppi.ph) [www.ppi.ph](http://www.ppi.ph)

**pazifik  
power**

[www.ppi.ph](http://www.ppi.ph)